

**SIN RUBTECH[®] POLYMER BOUND
PREDISPERSED SO-60G****Product Description**

Composition:	A proprietary predispersed 60% Soybean Oil in a 40% elastomeric / processing aids binder specially formulated for use in EPDM, NR, SBR, BR formulations
Appearance:	White to slight yellow Granules.
Density:	Approx. 1.12 g/cm ³ .
ML 1+4 @ 50°C	< 70
Moisture Content:	< 1.0 %
Melting Point:	~ N/A
Storage Stability:	At least 2 years under normal storage conditions.
Packing:	18 kg nett in sealed PE bag in a carton box.

Recommendations and Applications

Polymer bound predispersed SO-60G is recommended when a more eco friendly material, higher productivity and better dispersions required. This often translates to lower bottom-line costing.

Soybean Oil is one of the environmentally friendly alternatives to petroleum based oils.

Dosage

Start with direct 1:1 replacement by active ingredient for liquid soybean oil or liquid petroleum oils in formulation. Slowly reduce amount in formulation as there is no fly-loss in practical factory floor conditions.

SIN RUBTECH CONSULTANCY SDN BHD (Company No : 103451-P)

Contact Address : 10-12, Jalan Industri CheroK To'Kun 2, Taman Industri CheroK To'Kun, 14000 Bukit Mertajam, Malaysia.

Telephone : (604) 5511804

Fax : (604) 5514804

E-Mail : marketing@sinrubtech.com